

Data Sheet

Super Noise-Lock® W-58 Acoustic Window

IAC Acoustics
 IAC House, Electron Way, Chandlers Ford
 Hampshire, SO53 4SE, United Kingdom
 T: +44 (0) 1962 873 000
www.iacacoustics.global



Overview

- Certified acoustic performance rating
- Manufactured to standard and custom sizes
- Rugged all steel construction
- Finished in polyester powder coating as standard

Acoustic Rating

Rw (C; Ctr) 58 (-3; -8) dB to achieve minimum R'w56dB once installed (subject to flanking).

STC-58(dB) to achieve minimum NIC 56 once installed (subject to flanking).

Certified laboratory performance using standard 250mm (10") wall thickness arrangement as follows:

Frequency (Hz)	63	125	250	500	1k	2k	4k	8k
Full Octave Sound Transmission Loss (dB)	24	36	45	55	64	68	78	-

Standard Features



Acoustic Rated

Optional Extras



Fire Rated



Bullet Resistance



Angled Panes

Overview


IAC Acoustics produces an engineered system — custom-designed in house to suit the required opening of any given project. Utilising precision laser cutting and state-of-the-art fabrication, all IAC Super Noise-Lock® windows are simple to assemble on site by our network of highly experienced installation crews.

IAC Super Noise-Lock® windows are laboratory tested for performance in both IAC's own R&D facilities and independent laboratories, further supported by installed site testing. IAC Acoustics is renowned for quality, durability and guarantees in-field performance.

Design Features

IAC Super Noise-Lock® windows are available with a number of standard and custom design options. Please consult IAC Acoustics for availability of both standard and bespoke features such as angled panes, bullet resistant glass and EN 16 34-1 (EI) fire rated frames in various ratings from E30 to EI90. All IAC Super Noise-Lock® windows are built to order and site assembled using laminated safety glass as standard.

- ① 12.8mm laminated safety glass
- ② 12.8mm laminated safety glass
- ③ Acoustic foam ③a Optional perforated reveal
- ④ Host wall
- ⑤ Neoprene acoustic seal
- ⑥ Painted steel capping frame
- ⑦ Acoustic foam retainer



The relationship between the clear view and structural openings for both width and height is the same for all sizes of IAC Super Noise-Lock® W-58 windows. Measurements to consider can be seen in the table below.

	width	height
Structural Opening	X	Y
Clear View*	X - 66mm	Y - 66mm

* Clear view will decrease for fire rated frames, contact IAC Acoustics for details

Performance Features

- Acoustically de-coupled high performance steel acoustic window
- Architecturally aesthetic steel capping frame with secret fixings as standard
- Custom-built to order with various options for:
 - angled panes
 - fire resistance
 - bullet resistance

IAC Acoustics

IAC House
Electron Way
Chandlers Ford, S053 4SE

T: +44 (0) 1962 873 000
E: info@iac-uk.com

www.iacacoustics.global